



PHCC Pro Series B12-100 Maintenance Free/AGM Battery



Compatibility:

- PHCC Pro Series Backups
 - ◆ PHCC-1000
 - ◆ PHCC-1730*
 - ◆ PHCC-1850
 - ◆ PHCC-2400*
- PHCC Pro Series Combos
 - ◆ PS-C11
 - ◆ PS-C22*
 - ◆ PS-C33*

- Provide dependable service - without having to add battery fluid or distilled water
- Run the pump longer... for more hours per charge
- Works with all current PHCC Backup and Combination systems
- Last longer in standby operation

** Older versions, before 2014 of the PHCC-1730 and PHCC-2400 backup systems and the PS-C22 and PS-C33 combo systems that include the Remote Terminal are compatible with the Pro Series Maintenance Free/AGM Battery. Using a maintenance free battery with an older non-compatible system may cause false alarms.*

Industrial Grade for the Residential Market

www.StopFlooding.com

800-991-0466

PHCC Pro Series B12-100 Maintenance Free Standby Battery

Pumping Time*

| | B-1000** | B-2200** | B12-90 | B12-100 |
|-----------|-----------------|-----------|-----------|-----------|
| PHCC-1000 | 50 Hours | 100 Hours | 100 Hours | 110 Hours |
| PHCC-1850 | Not recommended | 60 Hours | 60 Hours | 70 Hours |
| PHCC-2400 | Not recommended | 50 Hours | 50 Hours | 55 Hours |

* Run time based on 10% duty cycle. Run times may vary based on water flow

** Battery fluid sold separately

Specifications

| | B-1000 | B-2200 | B12-90 | B12-100 |
|----------------------|---------------------------------------|--|------------------|------------------|
| Type of Battery | Wet Cell | Wet Cell | Maintenance Free | Maintenance Free |
| Height (Top of Post) | 9-1/4" | 10" | 9-1/2" | 8-7/8" |
| Length | 11-1/8" | 12-7/8" | 12" | 12" |
| Width | 6-1/2" | 6-5/8" | 6-1/2" | 6-1/2" |
| Voltage | 12 VDC | 12 VDC | 12 VDC | 12 VDC |
| Shipping Weight | 20.5 lbs. | 37 lbs. | 58 lbs. | 58 lbs. |
| Case Size | 24 | 31 | 27 | 27 |
| | 90 min. @ 25 Amps Reserve Capacity | 182 min. @ 25 Amps Reserve Capacity | 90 Amp hours | 100 Amp hours |

Extended Pump Run Time

Systems capable of extending run time***:

Battery Backup System

- PHCC-1850
- PHCC-2400

Combination System

- PS-C22
- PS-C33

| | (Two) B-2200** | (Two) B12-90 | (Two) B12-100 |
|-----------|----------------|--------------|---------------|
| PHCC-1000 | — | — | — |
| PHCC-1850 | 120 Hours | 120 Hours | 140 Hours |
| PHCC-2400 | 100 Hours | 100 Hours | 110 Hours |

* Run time based on 10% duty cycle. Run times may vary based on water flow

** Battery fluid sold separately

*** For extended run time, batteries should be of similar age, type and capacity

Parallel Jumper Cables

- Extend the run time of the PHCC-1850 and 2400 Battery Backups and the PS-C22 and PS-C33 Combo Systems
- Connects multiple PHCC Pro Series batteries
- 12 gauge wires, 40" length with 3/8" and 5/16" ring terminals



Available from: